



Part of the DB Group

## PRODUCT DATA SHEET

# PUDLO CD Plug / S

### DESCRIPTION

**PUDLO CD Plug / S** are plugs designed to be used in conjunction with the **PUDLO CD20 & CD08** Cavity Drain System. Thermoplastic Elastomer seals ensure complete water tightness of the system.

### USES

**PUDLO CD Plug / S** can be used in the following applications for both damp and waterproofing applications:

- **CD20 & CD08** membrane
- On brick
- On stone
- On concrete

### BENEFITS

- Works in conjunction with CD membrane systems
- Tailor made for system
- Available with or without seal (contact **PUDLO** for more information)
- Quick and easy to install
- 60mm length which is suitable for both single skin and cavity walls



### TECHNICAL

Performance	PUDLO CD Plug / S	
Concrete	0.55 kN	-
Solid Brick	0.5 kN	-
Lightweight Block	0.3 kN	-
Shear Loading	0.038 kN	-
Application Temperature °C	-20 to +90	-
Material	Plug High Density Polypropylene	Seal Thermoplastic Elastomer

### FIXINGS & SCREWS

In the 8 mm and 8 mm mesh drill a 10 mm hole using an SDS drill bit. Use a number 10 screw in the plug to fix battens or metal lining systems

### PACKAGING

**PUDLO CD Plug / S** is supplied as 200 plugs per box.



Part of the DB Group

## PRODUCT DATA SHEET

### ANCILLARY PRODUCTS

- **PUDLO Cavity Drain System (including ancillaries).**

### HEALTH & SAFETY

Please refer to **PUDLO CD Plug / S** MSDS for more information.

For further information on accessories that are used with **PUDLO CD Plug / S**, please contact **PUDLO** Head Office on 01954 780687 or email [sales@pudlo.com](mailto:sales@pudlo.com).