



Part of the DBGroup

PRODUCT DATA SHEET

PUDLO Membrane Granules

DESCRIPTION

PUDLO Membrane Granules is a granular sodium bentonite which is used as an ancillary product for sealing the **PUDLO Membrane BW**.

When wet and mixed with water these granules form into a low permeable paste.

USES

PUDLO Membrane Granules is used for the sealing of service penetrations through the **PUDLO Membrane BW** and concrete.

BENEFITS

- Easy to mix and quick to install.
- Fills cavities between the service penetration and **Membrane BW**.



TECHNICAL DATA

Application	Rate
Wall / Footing Fillet – 38mm	8.0 l/m (approx.); dry granules 2.0 l/m (approx.); granules mixed with water form a paste
Road Deck Layer – 3mm	70 sq ft (6.5 sq m)

SURFACE PREPARATION

- Surface should be free from dirt / debris and loose particles
- **PUDLO Membrane Granules** should not be applied on standing water.

PACKAGING

20kg bag

ANCILLARY PRODUCTS

- **PUDLO Membrane BW**

PHYSICAL & CHEMICAL PROPERTIES & HAZARDS

For chemical properties please refer to **PUDLO Membrane Granules** MSDS

HEALTH & SAFETY

Product should be used with adequate ventilation and avoid breathing in dust. All workers using this product should wear the correct PPE and approved breathing apparatus. Avoid skin and eye contact and do not ingest. Refer to **PUDLO Membrane Granules** MSDS for all other safety information.

For further information on accessories that are used with **PUDLO Membrane Granules** please contact PUDLO Head Office on 01954 780687 or email sales@pudlo.com