



Part of the DB Group

PRODUCT DATA SHEET

PUDLO Rawtape

DESCRIPTION

PUDLO Rawtape is a cross-weave glass fibre reinforced tape coated with a synthetic rubber resin adhesive (hottmelt).

USES

PUDLO Rawtape is used to seal **PUDLO Rawmat SS** (post applied system) membrane overlaps.

BENEFITS

- Quick and easy to install
- Seals membrane overlaps

TECHNICAL DATA

Total thickness: 0.125mm
Backing thickness: 0.03mm
Tensile strength: 240n/cm
Elongation: 10%
Temperature: 0 - 60°C
Steel adhesion: 5n/cm

INSTALLATION

PUDLO Rawtape is applied to the outer polyethylene film, ensuring coverage of 50mm each side of the overlap line.



PACKAGING

PUDLO Rawtape comes in 18 rolls supplied per box.

Colour: Clear
Roll length: 50m
Roll width: 100mm

ANCILLARY PRODUCTS

- **PUDLO Rawmat SS**

HEALTH & SAFETY

Refer to **PUDLO Rawtape** MSDS for more information.

For further information on accessories that are used with **PUDLO Rawtape** please contact **PUDLO** Head Office on 01954 780687 or email sales@pudlo.com.