

NBS PLUS MANUFACTURER'S PRODUCT PAGE

Product name: PUDLO Liquid Tank



Product summary:

Latex-based waterproofing liquid.

Product general description:

Latex-based waterproofing liquid, applied internally or externally to prevent the passage of water and moisture into buildings.

Features and benefits:

- Easy to apply.
- Can be brush, roller or spray applied.
- Provides an effective waterproofing and moisture vapour barrier.
- Conforms to the requirements of BS 8102: 2009 as a Type A system.

Applications:

Suitable for:

- All aspects of waterproofing where Grade 2 and 3 environments are required as part of a single or dual system in accordance with BS 8102: 2009.
- Can be used as a damp proofing membrane (DPM) on floors and walls.

PUDLO supplies a 120 mm x 5 m reinforcing strip with every three tubs for detailing around upstands and changes in level or angles.

Typically dries within two hours. The second coat should be applied within 24 hours of the first coat. Where multiple coats are applied, it is recommended that the coats are applied at right angles to each other. Consult manufacturer for details on recommended substrate preparation.

Product specification clause

Product reference:

[PUDLO Liquid Tank](#)

Product properties:

- Accessories/ Other requirements:

[Not required](#)

[PUDLO Detailing Strip](#)

End of product specification clause

As standard:

Thickness:

>1 mm.

Colour:

Green.

Technical characteristics:

- Coverage: 7.5 m² (per 15 kg tub).
- Form: Viscous liquid.
- Chemical composition: Advanced styrene-butadiene-styrene (SBS) with specialty additives.
- Water tightness (to EN 1296, EN 1367, EN 1928): Pass.

Options:

No optional features

Approvals:

No approvals